



STONE **PROFESSIONAL**

CALIBER

POLISHING POWDER

FORMULATED FOR

ALL CALCITE-BASED
STONE & TERRAZZO

WET TO DRY POLISH

Saves Time
Reduces Clean-up

MB-12
FOR PROFESSIONAL USE ONLY



**POLISH TO
A DEEP GLOSS**

MB-12 is an amazing performer that polishes to a deep gloss—often higher than from the factory —all Marbles, Travertine, Serpentine (green marble), Onyx, Limestone, Alabaster, Ophicalcite, Terrazzo and more! Also works great for cleaning and removing coatings or sealers from Granite!

APPLICATION:

Stone countertops & floors

COUNTERTOPS: Target an area of approximately 2 - 3 sq. ft. Sprinkle ¼ teaspoon of MB-12 on the surface to be polished in a circular pattern, slightly smaller than the polishing pad to be used. Using a spray bottle, add enough water to the powder to soak the powder. Use a white polishing pad with a right-angle grinder/polisher (variable speed is a MUST). Set the speed to low. Place pad on top of powder mixture. While controlling the speed with the trigger and applying as much pressure as the machine can take, start spreading the slurry over the targeted area, keeping a very low RPM, until it's almost dry. Pull the trigger all the way while gradually lightening the pressure and buff to a shine while moving the machine swiftly over the targeted area. Remove any streaking with a clean dry white pad and a mist of water.

FLOORS: Target an area of approximately 10 – 12 sq. ft. and sprinkle 1 tablespoon of MB-12 in the center of area in a circular pattern slightly smaller than the diameter of the floor machine. Using a spray bottle, add enough water to the powder to soak the powder. Using a hog's hair pad and a floor machine with at least 1.5 hp and not exceeding 175 RPM, swiftly swing the machine side to side over target area



to evenly spread the product slurry. Then polish slowly with a spiral motion, moving from one end of the targeted area to the other and back until the slurry is dry and the stone surface becomes shiny. The first area will probably need to be done a couple of times for proper pad build-up. We suggest not exceeding approx. 100 sq. ft. with one side of the pad. After that, flip the pad over and go another 100 sq. ft. or so (hog-hair pads can be hosed off a couple of times and reused, before disposal.) Remove any streaking with a clean dry hog's hair pad and a mist of water.

MB Stone Care & Supply, LLC
2301 Industrial Park Dr.
Wilson, NC 27893
888-509-5831 • www.mbstonepro.com